

COPYRIGHT 2021
 THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH REMAINS THE PROPERTY OF CHIPOTLE MEXICAN GRILL, INC.. PERMISSION FOR USE OF THIS DOCUMENT IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN AGREEMENT WITH CHIPOTLE MEXICAN GRILL, INC..



CHIPOTLE MEXICAN GRILL, INC.
 PO BOX 182566
 COLUMBUS, OH 43218-2566
 TELEPHONE: (614) 318-2400
 INTERNET: WWW.CHIPOTLE.COM

STORE NO.: 4251
 NORTH VALDOSTA
 3289 INNER PERIMETER RD.
 VALDOSTA, GA 31605

Issue Record:

12.20.2021	PERMIT SET
07.06.22	BID SET
08.26.22	CONSTRUCTION SET

Revisions:

#	Date	Description
2	07/07/2022	REV 3 DB_03
3	08/18/2022	RTU Update

Drawn: GPD Checked: QAQC

GPD Project No. 2021201.25 CMG Store No. 4251

Contents:
 HVAC SCHEDULES

M600

CONTROL FUNCTIONS

- THE MAIN COOKING EXHAUST FAN AND MAKE-UP AIR UNIT SHALL BE INTERLOCKED TO OPERATE TOGETHER. THIS CONTROL CIRCUIT IS ACTIVATED BY A SWITCH AND INCLUDES A FIRE PROTECTION OVERRIDE.
- THE TEMPERATURE IN EACH ZONE IS CONTROLLED BY SPACE TEMPERATURE SENSORS CONNECTED TO THE THERMOSTATS LOCATED IN THE OFFICE. ALL ZONES SHALL OPERATE WITH CONTINUOUS FAN OPERATION DURING OCCUPIED TIMES AND INTERMITTENTLY AS NEEDED TO MAINTAIN SET POINTS DURING UNOCCUPIED TIMES. OUTSIDE AIR DAMPERS SHALL BE OPEN CONTINUOUSLY WHEN EITHER IN OCCUPIED MODE OR WHEN THE HOOD SYSTEM IS ON AND SHALL BE CLOSED DURING UNOCCUPIED PERIODS.
- THE THERMOSTATS SHALL DETERMINE OCCUPIED/UNOCCUPIED STATUS BASED ON THE SCHEDULE IN THE ENERGY MANAGEMENT SYSTEM.

AIR BALANCE SCHEDULE

TAG	SUPPLY FLOW	RETURN FLOW	EXHAUST FLOW	SUBTOTAL
EF-1	0 CFM	0 CFM	3,200 CFM	-3,200 CFM
EF-2	0 CFM	0 CFM	150 CFM	-150 CFM
MAU-1	1,950 CFM	0 CFM	0 CFM	1,950 CFM
RTU-1	3,400 CFM	2,900 CFM	0 CFM	500 CFM
RTU-2	4,000 CFM	3,000 CFM	0 CFM	1,000 CFM
NET PRESSURIZATION				100 CFM

AIR TERMINAL SCHEDULE

TAG	DESCRIPTION	FACE SIZE	MATERIAL	FINISH	MOUNTING	FURNISHED BY	INSTALLED BY	BASIS FOR DESIGN		NOTES
								MANUFACTURER	MODEL	
BS1	BATHROOM AIR PURIFICATION UNIT		STAINLESS STEEL	STAINLESS STEEL	SURFACE MOUNT	TUV	GC	RGF ENVIRONMENTAL GROUP	BRU ASSEMBLY	SEE ELECTRICAL SHEETS FOR CONNECTION INFORMATION
CD1	PERFORATED CEILING DIFFUSER	24" X 24"	ALUMINUM	WHITE	LAY-IN CEILING	GC	GC	NAILOR	4320A TYPE L	PROVIDE WITH INTEGRAL OBD
CD2	PERFORATED CEILING DIFFUSER	12" X 12"	ALUMINUM	WHITE	LAY-IN CEILING	GC	GC	NAILOR	4320A TYPE S	PROVIDE WITH INTEGRAL OBD, REMOVE 4-WAY DEFLECTORS
ER1	PERFORATED CEILING EXHAUST	12" X 12"	ALUMINUM	WHITE	SURFACE MOUNT	GC	GC	NAILOR	4330R TYPE S	PROVIDE INTEGRAL OBD
RG1	PERFORATED CEILING RETURN	48" X 24"	ALUMINUM	WHITE	LAY-IN CEILING	GC	GC	NAILOR	4330R TYPE L	
RG3	PERFORATED CEILING RETURN	48" X 24"	ALUMINUM	WHITE	SURFACE MOUNT	GC	GC	NAILOR	4330R TYPE S	
SR1	ADJUSTABLE TURBO NOZZLE	SEE NECK SIZE	ALUMINUM	WHITE	WALL	GC	GC	SEIHO	NT14	PROVIDE WITH FACE-ACCESSIBLE OBD
SR2	DOUBLE DEFLECTION SUPPLY REGISTER	SEE NECK SIZE	ALUMINUM	WHITE	WALL	GC	GC	NAILOR	51DH	PROVIDE WITH INTEGRAL OBD

FAN SCHEDULE

TAG	DESCRIPTION	AIRFLOW	E.S.P.	WEIGHT	ELECTRICAL		FURNISHED BY	INSTALLED BY	BASIS FOR DESIGN		REMARKS
					MOTOR POWER	V/P/H			MANUFACTURER	MODEL	
EF-1	UPBLAST UL762 EXHAUST FAN	3,200 CFM	1.20 in-wg	400 lb	3 hp	208/3/60	HS	GC	CAPTIVE-AIRE	DU240HFA	DIRECT DRIVE UL762 UPBLAST EXHAUST FAN FURNISHED WITH WEATHERPROOF DISCONNECT AND VENTED ROOF CURB
EF-2	DOWNBLAST RESTROOM EXHAUST FAN	150 CFM	0.60 in-wg	100 lb	0.18 hp	120/1/60	HS	GC	CAPTIVE-AIRE	DR12HFA	DIRECT DRIVE DOWNBLAST RESTROOM EXHAUST FAN FURNISHED WITH INTEGRAL DISCONNECT, SPEED CONTROL, BACKDRAFT DAMPER, AND CURB

VIROGUARD SCHEDULE

TAG	COUNT	DESCRIPTION	DUCT CONNECTION SIZE	FAN	FURNISHED BY	INSTALLED BY	BASIS FOR DESIGN
VG-1	1	VIROGUARD HOOD EXHAUST FAN ROOFTOP CONTAINMENT SYSTEM	18" X 18"	CAPTIVE-AIRE DU240HFA	TDC	GC	ENVIROMATIC

CONDENSING UNIT SCHEDULE

TAG	DESCRIPTION	NOMINAL CAPACITY	NUMBER OF		REFRIGERANT		WEIGHT	ELECTRICAL			FURNISHED BY	INSTALLED BY	BASIS FOR DESIGN		REMARKS
			COMPRESSORS	CIRCUITS	TYPE	CHARGE		MOCP	FLA	V/P/H			MANUFACTURER	MODEL	
CU-1	CONDENSING UNIT - WALK-IN COOLER		1	1	R-404A	10.4 lb	250 lb	15 A	9 A	208/3/60	WCS	GC	HARFORD	KPCL99MZOP-3E	FURNISHED WITH WALK-IN COOLER
CU-2	REMOTE CONDENSER - LOW CAPACITY ICE MAKER		0	1	R-404A	11.46 lb	100 lb			120/1/60	KES	GC	HOSHIZAKI	URC-9F	FURNISHED WITH ICE MAKER
CU-3	REMOTE CONDENSER - SODA MACHINE ICE MAKER		0	1	R-404A	3.86 lb	100 lb			120/1/60	KES	GC	HOSHIZAKI	URC-5F	FURNISHED WITH ICE MAKER

MAKEUP AIR UNIT SCHEDULE

TAG	DESCRIPTION	AIRFLOW	E.S.P.	HEATING			WEIGHT	ELECTRICAL		FURNISHED BY	INSTALLED BY	BASIS FOR DESIGN		REMARKS
				INPUT	OUTPUT	EAT		MOTOR POWER	V/P/H			MANUFACTURER	MODEL	
MAU-1	DIRECT-FIRED MAKEUP AIR UNIT	1,950 CFM	0.80 in-wg	225,000 Btu/h	220,000 Btu/h	21 °F	650 lb	2 hp	208/3/60	HS	GC	CAPTIVE-AIRE	A1-D.250-G10	12.5:1 MAX TURNDOWN. FURNISHED WITH DISCONNECT, ROOF CURB, SCREEN INTAKE, AND WASHABLE ALUMINUM FILTERS

KITCHEN HOOD SCHEDULE

TAG	DESCRIPTION	MAX COOKING TEMP.	EXHAUST PLENUM							PERFORATED SUPPLY PLENUMS							NO. OF LIGHT FIXTURES	WEIGHT	FURNISHED BY	INSTALLED BY	BASIS FOR DESIGN		REMARKS		
			DUCT COLLARS							MAU PLENUM			AC PLENUM								MANUFACTURER	MODEL			
			AIRFLOW	E.S.P.	NO.	WIDTH	LENGTH	LENGTH	WIDTH	LENGTH	WIDTH	AIRFLOW	NO.	WIDTH	LENGTH	AIRFLOW								NO.	DIAMETER
HD-1	TYPE I CANOPY HOOD WITH PERFORATED MAU AND AC SUPPLY PLENUMS	600 °F	3,200 CFM	0.86 in-wg	2	10"	1' - 3"	14' - 3"	4' - 3"	15' - 3"	1' - 10"	1,950 CFM	4	10"	2' - 0"	800 CFM	7	8"	10	1,200 lb	HS	GC	CAPTIVE-AIRE	5424 ND-2-ACPS-P	MAT'L: 18 GA. TYPE 430 SS. FURNISHED WITH VAPORPROOF INCANDESCENT LIGHT FIXTURES, 16" TALL HE SS FILTERS, INTEGRAL UTILITY CABINET, ANSUL SYSTEM, DUCT COLLAR TEMPERATURE SENSOR, PREWIRE PACKAGE, SPARE FIRE SYSTEM DRY CONTACT, AND 4-POLE 20A CONTACTOR

ROOFTOP UNIT SCHEDULE

TAG	DESCRIPTION	NOMINAL CAPACITY	EER	AIRFLOW			NET COOLING CAPACITY					HEATING CAPACITY			NUMBER OF		REFRIGERANT		ELECTRICAL			BASIS FOR DESIGN		REMARKS			
				TOTAL	OA	E.S.P.	TOTAL	SENSIBLE	DB	WB	COND. EAT	INPUT	OUTPUT	EAT	COMPRESSORS	CIRCUITS	TYPE	CHARGE	WEIGHT	MOCP	FLA	V/P/H	FURNISHED BY		INSTALLED BY		
				500 CFM <th>0.80 in-wg <th>103,000 Btu/h <th>81,000 Btu/h <th>80 °F <th>67 °F <th>95 °F <th>125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th>	0.80 in-wg <th>103,000 Btu/h <th>81,000 Btu/h <th>80 °F <th>67 °F <th>95 °F <th>125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th>	103,000 Btu/h <th>81,000 Btu/h <th>80 °F <th>67 °F <th>95 °F <th>125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th>	81,000 Btu/h <th>80 °F <th>67 °F <th>95 °F <th>125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th></th></th></th></th>	80 °F <th>67 °F <th>95 °F <th>125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th></th></th></th>	67 °F <th>95 °F <th>125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th></th></th>	95 °F <th>125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th></th>	125,000 Btu/h <th>100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th></th>	100,000 Btu/h <th>57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th></th>	57 °F <th>2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th></th>	2 <th>2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th></th>	2 <th>R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th></th>	R-410A <th>17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th></th>	17.3 lb <th>1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th></th>	1,335 lb <th>50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th></th>	50 A <th>45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th></th>	45 A <th>208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th></th>	208/3/60 <th>HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th></th>	HES <th>GC <th>CARRIER</th> <th>48HCDE09</th> </th>	GC <th>CARRIER</th> <th>48HCDE09</th>		CARRIER	48HCDE09	
RTU-1	KITCHEN ROOFTOP UNIT	8.5 ton	12	3,400 CFM	500 CFM	0.80 in-wg	103,000 Btu/h	81,000 Btu/h	80 °F	67 °F	95 °F	125,000 Btu/h	100,000 Btu/h	57 °F	2	2	R-410A	17.3 lb	1,335 lb	50 A	45 A	208/3/60	HES	GC	CARRIER	48HCDE09	FURNISHED WITH COMP. ENTHALPY ECON., BAROMETRIC RELIEF, SUP. SMOKE DETECTOR W/ REMOTE KEYED ANNUNCIATOR/RESET, M.O.D., MERV-8 FILTERS, CURB, HAIL GUARD, TOOLLESS HINGED ACCESS PANELS, DISCONNECT, & UNIT-MOUNTED CONVENIENCE RECEPTACLE, REHEAT. PROVIDE WITH HUMIDI-MIZER.
RTU-2	DINING ROOM ROOFTOP UNIT	10 ton	12	4,000 CFM	1,000 CFM	0.80 in-wg	119,800 Btu/h	92,500 Btu/h	80 °F	67 °F	95 °F	180,000 Btu/h	144,000 Btu/h	57 °F	2	2	R-410A	15.8 lb	1,335 lb	70 A	57 A	208/3/60	HES	GC	CARRIER	48HCDE11	FURNISHED WITH COMP. ENTHALPY ECON., BAROMETRIC RELIEF, SUP. SMOKE DETECTOR W/ REMOTE KEYED ANNUNCIATOR/RESET, M.O.D., MERV-8 FILTERS, CURB, HAIL GUARD, TOOLLESS HINGED ACCESS PANELS, DISCONNECT, & UNIT-MOUNTED CONVENIENCE RECEPTACLE, REHEAT. PROVIDE WITH HUMIDI-MIZER.