LUDE AN ALLOWANCE TO COVER ALL SUCH MODIFICATIONS.

OF CEILING DIFFUSERS & REGISTERS SEE ARCHITECTURAL
LAN. IF THE PLAN DO NOT ACCURATELY REFLECT THE JOB
CONSTRUCTION IS NOT PER PLANS, NO MECHANICAL INSPECTION
ADDENDUM APPROVED BY THE BUILDING DEPARTMENT IS

DUCT DROPS FROM UNIT MIN 8'-0" SHALL BE INTERNALLY
DUCTWORKS SHALL ALSO BE LINED. DUCT SIZES SHOWN ARE
ONG ONLY. FABRICATE AND SIZE DUCTWORKS ACCORDING TO
NSULATION REQUIREMENTS.

UME DAMPERS TO ALL SUPPLY, RETURN AND MAKE-UP AIR

TO ALL "GREASE" DUCTS.

SOR IN THE RETURN PLENUM AND ALL THERMOSTAT/CONTROLS
THE OFFICE.

R OR FIRE SMOKE DAMPER FOR ANY SUPPLY AND RETURN
TES ANY RATED WALL, CEILING OR ANY RATED SHAFT.
E DAMPERS, FIRE OR FIRE SMOKE DAMPERS SHALL BE
IME. PROVIDE A DEDICATED ACCESS PANEL WHERE REQUIRED.

7 14"X14" EXHAUST AIR DUCT UP THRU ROOF TO EF-6. (1400 CFM)

15 22"X10" GREASE EXHAUST AIR DUCT CONNECTION TO HOOD#-5. (2400 CFM)

23 24"X10" MAKE UP AIR DUCT CONNECTION TO WOK HOOD#-7. (960 CFM)