



1. EXISTING ROOFTOP UNIT CONTRACTOR TO VERIFY ANY DEFICIENCIES TO OWN ROOFTOP UNIT SCHEDULE REQUIREMENTS. REMOVE BACK TO DUCT RISER AND
2. ABANDON EXISTING ROOF OTHER TRADES TO DISCONNECT REMOVE ALL ASSOCIATED 6" BELOW ROOF PENETRATIONS. REMOVE INSULATION.
3. DEMO ALL UNUSED HVAC CAP.
4. NEW EXHAUST FAN TO BE SHOWN. REUSE EXISTING ADAPTER. BALANCE FAN
5. PROVIDE RETURN AIR DUCT ELBOW DUCT FOR SOUND RTU OPENING.
6. RELOCATE EXISTING THERM ON PLAN. PROVIDE NEW TO ACCOMMODATE NEW I CONTROLLER PER MANUF
7. PROVIDE RETURN AIR GR INSULATED BOOT FOR SC MINIMUM SIZE OF BOOT
8. LOCATE UNIT HEATER ON PER MANUFACTURER'S R
9. LOCATE SUPPLY GRILLE TOWARD IT EQUIPMENT L
10. LOCATE AIR CURTAIN WH ARCHITECT FOR MOUNTING ACCORDING TO MANUFACT INSTRUCTIONS.