



KEY NOTES

- 1) ROUTE THE STATION OF THE DUCT THROUGH THE ROOM TO THE EXISTING DUCT. THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 2) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 3) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 4) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 5) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 6) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 7) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 8) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 9) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 10) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 11) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 12) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 13) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 14) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.
- 15) THE DUCT SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED AND SHALL BE INSTALLED IN THE ROOM TO BE MAINTAINED.

PERMITTING NOTE:

ALL REFRIGERATION EQUIPMENT INCLUDING UNDER REFRIGERATORS WILL BE SUBMITTED UNDER

GENERAL NOTE:

- A. MECHANICAL CONTRACTOR SHALL ADVISE TO A GENERAL CONTRACTOR VERTICAL FLOW, ADJUST TO AVOID AIRFLOW ON SENSORS, REFRIGERATION FOOD REFRIGERATION EQUIPMENT.
- B. IN ADDITION TO SPECIFICATIONS REQUIRE BALANCING, SUBMIT TESTING AND BALU INDICATING LOCATION OF INLETS AND THE TESTING AND BALANCING REPORT.
- C. CONTRACTOR SHALL BE RESPONSIBLE DAMPERS IN LOCATIONS ACCESSIBLE

JANITOR'S CLOSET