

MECHANICAL DRAWINGS.
 COMPLIANCE WITH
 IN. HOOD SHALL
 AUTOMATICALLY ENERGIZE
 IF DETECTED.
 WATER AND AIR
 PER DETAILS 2, 4,
 SPECIFIC FOR TESTING

AS DETAILED IN THE
 LINE SET,
 CONTROL, SIGHT
 AND
 MANUFACTURER'S
 LISTING STANDARD 15.
 3' OF THE
 REFRIGERANT LINE
 PROTECTIONS AFTER

AS DETAILED IN THE
 LINE SET,
 CONTROL, SIGHT
 AND
 MANUFACTURER'S
 LISTING SHALL
 BE INSTALLED UNDER
 REFRIGERANT PIPING TO ICE
 MELT SHROUD AS

SEE INSTRUCTIONS AND
 THE ARCHITECTURAL
 DRAWINGS FOR FINISHES
 UNLESS OTHERWISE

SEE SCHEDULE 1/M700. TYPICAL.
 WITH REMOTE KEY
 SWITCH UNIT 60" AFF.

SEE SCHEDULE 6/M700. SEE
 ELECTRICAL FOR WARNING
 LIGHTS AND DOOR(S)

SEE SCHEDULE 10 AND OUTSIDE AIR
 INTAKE FOR POSITION AIR INTAKE
 FOR MORE INFORMATION

SEE SCHEDULE 12 FOR THE OTHER SIDE OF ROOM AT

SEE SCHEDULE 12 FOR
 OTHER SIDE OF ROOM AT

