



**GENERAL NOTES**

- KEY NOTES**
1. GENERAL NOTES
  2. NON-LOCATION OF PLACES OR AREAS, RELIEF VENT LOCATIONS, HOODS, ETC. WHOSE EXACT LOCATION IS NOT KNOWN, SHOULD BE LOCATED IN ACCORDANCE WITH THE GENERAL NOTES AND THE GENERAL NOTES. GENERAL NOTES TO APPLICABLE.
  3. RELIEF VENT LOCATIONS OF THROUGH ROOF TOP ROOFING SHOULD BE LOCATED IN ACCORDANCE WITH THE GENERAL NOTES.
  4. HOODS AND CAPS SHALL BE CONNECTED TO APPROVED EXHAUST FLOWING OUTSIDE.
  5. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.
  6. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.
  7. ELECTRICAL TO BE IN ACCORDANCE WITH THE GENERAL NOTES.
  8. NOT USED
  9. NOT USED
  10. NOT USED
  11. DUCTS TO BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. DUCTS TO BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. DUCTS TO BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.
  12. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.
  13. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.
  14. NOT USED
  15. NOT USED
  16. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.
  17. NOT USED
  18. NOT USED
  19. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.
  20. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE. HOODS SHALL BE CONNECTED TO THE EXHAUST WITH NEARLY SILENT FLOWING OUTSIDE.

**CR**  
 CONSULTING ENGINEERS  
 1000 N. 17th St., Suite 1000  
 Phoenix, AZ 85016  
 (602) 955-1000  
 www.crcorp.com

**Kroger**  
 Kroger Engineering  
 1000 N. 17th St., Suite 1000  
 Phoenix, AZ 85016  
 (602) 955-1000  
 www.kroger.com

**PROJECT TITLE** PHASE 02  
**N-881**  
 881 HAMPSTEAD VILLAGE TX  
 1000 N. 17th St., Suite 1000  
 Phoenix, AZ 85016  
 (602) 955-1000  
 www.kroger.com  
**DATE** 3/31/2018  
**TYPE** HVAC PLAN  
**SCALE** M1.1